

5VDC Power Supply
Part no. PWR5V



AC-DC adapter. This is a standard 5VDC 1000mA power supply compatible with US power plugs. It can be used with our serial converters and all other products requiring a stable 5VDC supply.

SPECIFICATIONS	
Input	AC input voltage: 110 -120 VAC AC input frequency: 47Hz ~ 63Hz AC input current: 0.3A max. Max. inrush current: 30A max. Leakage current: max. 0.75 mA Efficiency: 70% typical at full load No load power consumption 0.5w
Output	DC output voltage: +5VDC Load min: 0.0A Load max: 1.0Av
Polarity	Center +
Protection	Short circuit protection: automatic recovery
Environment	Operating temperature: 0 to 40 degrees C
Humidity	20% to 80% RH Storage temperature: -20 to +70 degrees C Storage humidity: 10% to 90% RH
Mechanical	Standard plastic case 50(L) x 25(W) x 28.5(H)mm Output Jack: 5.5 x 2.1 x 11.5mm
HTS	8517.18.0050

To access technical support, please visit the U.S. Converters website at:
www.USconverters.com
Here you will find:

- Latest drivers and updates for download
- Technical tips
- Documentation
- Configuration support
- and much more...

Feel free to contact our technical support team at mail@usconverters.com with any issues.

Copyrights © U.S. Converters