

Device Information

Device Name	WSDEV0001	Firmware Version	V1. 452	Device MAC	28-76-E4-84-19-72
-------------	-----------	------------------	---------	------------	-------------------

Network Settings

Device IP	192.168.1.200	Device Port	4196	Device Web Port	80
Work Mode	TCP Server ▼	Subnet Mask	255.255.255.0	Gateway	192.168.1.1
Destination IP/DNS	192.168.1.3	Destination Port	4196	IP mode	Static ▼

Serial Settings

Baud Rate	115200 ▼	Databits	8 ▼	Parity	None ▼
Stopbits	1 ▼	Flow control	None ▼		

Advanced Settings

No-Data-Restart	Disable ▼	No Data Restart Time	300 second	5~1270	Reconnect-time	12	1~255 second
-----------------	-----------	----------------------	---------------	--------	----------------	----	--------------

Multi-Host Settings

Protocol	None ▼	Instruction Time out	0	32~8000ms	Enable Multi-host	No ▼
RS232/485/422 Conflict Time Gap	0 5~255ms					

NOTE: 1. Multi-host is always enabled when Protocol is Modbus TCP to RTU. 2. Time out is always 0 when Multi-host is disabled.

3. Time out only can be set as mulitpy of 32.

Modify Web Login Key

New Key		Input Key Again			
---------	--	-----------------	--	--	--

Submit