

Firmware Upgrade

Serial To Ethernet Converter - Microsoft Internet Explorer

File Edit View Favorites Tools Help

Back Forward Stop Home Search Favorites Media RSS Mail Print

Address http://192.168.0.125/ Go Links >>

TCP/IP Converter

One Page Quick Setup (Fixed IP)

TYPE: STATIC IP

IP Address	192 . 168 . 0 . 125
Subnet mask	255 . 255 . 255 . 0
Gateway	0 . 0 . 0 . 0
Primary DNS	168 . 95 . 1 . 1

Serial Port Mode

Serial Type	RS232
Baud Rate	19200

Connection Mode	TCP SERVER
Connection Port Number	50000
Remote Host IP Address (For Client Only)	0 . 0 . 0 . 0

APPLY CANCEL BACK

Done Internet

Main Menu

- One Page Setup

Advanced Setup


- Operation Mode
- Serial Type
- Dynamic DNS

Management

- Device Admin
- System Status
- Backup & Restore
- Upgrade Firmware
- Ping


1. Click Upgrade Firmware to enter firmware upgrade window

【Picture 05】




【Picture 06】


Select the .bin file.




【Picture 07】




【Picture 08】



【Picture 09】




【Picture 10】




【Picture 11】


Select the file ending with _IMAG



【Picture 12】



【Picture 13】



【Picture 14】

CHIYU Serial To Ethernet Converter - Microsoft Internet Explorer

File Edit View Favorites Tools Help

Back Forward Stop Home Search Favorites Media

Address http://192.168.0.126/ Go Links

BF-430

Main Menu

- One Page Setup

Advanced Setup

- Operation Mode
- Serial Type
- Dynamic DNS

Management

- Device Admin
- System Status
- Backup & Restore
- Upgrade Firmware
- Ping

Device Administration Setting

Block Standard Http Port(80) Management	<input checked="" type="radio"/> UNBLOCK <input type="radio"/> BLOCK	APPLY
Device Management IP Address	192 . 168 . 200 . 200	
Device Hostname		
Device Location		
Administrator Password	User Name Password Change Password Confirm	APPLY
Block Ping Request	<input checked="" type="radio"/> UNBLOCK <input type="radio"/> BLOCK	APPLY
MAC Address Change	00 : 00 : 00 : 00 : 00 : 00	APPLY
Reset System to Factory Default	FACTORY DEFAULT	
Reboot System	REBOOT	

1. Click Device Admin

2. Click FACTORY DEFAULT

Done Internet